MHM GEN **MGTP 20 USY HVO**

Event Ready 20kVA Diesel Generator

GPS Telemetry

Tracker

APPROVED When looking for a robust, reliable, good quality ultra silenced 20kVA generator, our MGTP 20 USY has everything the event market requires.

((0))

Bund Alarm

Optional extras:

Road-tow Kit

Features Benefits

20kVA 3ph (400V)

Linz alternator
Yanmar diesel engine (Stage 3A)
HVO (Hydrotreated Vegetable Oil) fuel approved
Exclusive MHM-Gen engine protection shutdown system
3 way fuel valve
12V battery isolator switch
Emergency stop button
Central lifting eye and fork pockets
Variable RCD
Fully bunded base (110%)

Engine oil drain pump

	of power to meet the demands of event hire
Heavy	duty and proven reliability
World	class performance and watercooled
	ble to run off either diesel, or a mixture of both fuels
high e	case of low fuel, low oil pressure, engine temp and battery e failure
Easy c	connectivity to an external fuel tank
Reduc	es flat battery breakdowns
Amus	st on any UK site
Flexib	le and safe lifting on site
Flexib	le protection
To ret	ain all spilt fluids
Reduc	cing service time

Three Phase Power (400V)

20kVA/ 16kW

=55

23 4.6 300

214)5kg wire cility



ULTRA SILENCED

FUEL

Specification

Ρ	e	rf	0	rı	m	n	C

						,	
Alternator	Linz (AVR Controll	ed)		Noise Level		LWA=80	dBa@7m=
Single Phase Power (110V) N/A			Insulation C	lass			
Single Phase Power (23	0V) 6.6kVA/ 5.3	kW		Mechanical	Protectic	ın - IP	
Engine			Fuel	Consumptio	n @ 75%	Load (Litr	es/hour)
Make	Yamnar		Fuel	Tank Capacit	y (Litres)		
Туре	TBA (Stage 3A)		Avei	rage Runtime	e (Hours)		
Fuel Diesel / HVO (HVO	= BS EN 15940:2016 Only)		@1	00%	53	@75%	
Number of Cylinders	4		@5	0%	107	@ 25%	
Power (HP)	27		(02	Per Hour @ 7	75% Load	ł	12.0
Engine Speed (RPM)	1500		Con	trol Panel	Dee	psea 731() c/w two v
Cooling	Water	_	CON	liorPatter		Auto Star	t/ Stop fac

Dimensions (Machine only)						
Length: 2300 mm	nm	Height: 1600 mm				
Dry Weight (No Fuel): 1250 k	Wet Weight	Wet Weight (Fuel Full): 1493 kg				
Dimensions (With road-tow kit)						
Length: TBA mm	Width: TBA mm Height: TBA mm					
Dry Weight (No Fuel): TBA kg Wet Weight (Fuel Full): TBA kg						
Socket	3ph (400V)	1ph	(230V)			
Configuration	32A	32A	16A			
MGTP 20 USY	1	2	2			
Hard wire facility	3ph (400V)	1ph	1ph (230V)			
MGTP 20 USY	~		✓			

Designed in the UK,

built in Italy

For more details call MHM TODAY on 0808 168 9099

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk





GROUP

f) () (in) (0)