


# ROAD-TOW PRESSURE WASHER BOWSER 2000-D

2000 litre/ 450 gallon road-towable pressure washer bowser suitable for general washing and cleaning on and off site



When looking for a robust, reliable, good quality road-tow water washer bowser, look no further than our MHM Road-Tow Pressure Washer Bowser 2000-D.



**Optional extras:**

-  Tap Kit
-  Multiple Colour Options Available
-  Hose Kit
-  Site-Tow Trailer
-  Skid Base

## TANK & CHASSIS Features

- 2000 litre capacity
- Internal anti-surge baffle
- 22 inch lockable top access cover
- Inner sealed and vented lid
- Protective galvanised base and durable corrosion free polyethylene inner and outer tank secured by 2 x stainless steel straps
- Lifting points
- Complete on road-tow chassis

## PRESSURE WASHER Features

- 3000 PSI/ 200 Bar
- Interpump water pump
- Return to tank unloader valve
- 1450rpm gearbox drive
- Yanmar diesel engine
- Strong protective metal frame
- Hand lance holder & hose storage
- Detergent/chemical feed-line c/w strainer filter

## Benefits

- Can be safely transported full of water and enough storage for most construction site applications
- Additional stability for transport
- Secure and simple refill access
- Extra protection
- Robust, long lasting & ready for work in any environment
- For flexible & safe loading & unloading (only lift when tank is empty)
- Single axle, suspension, brakes, mudguards & rear lights – *suitable for UK highway use*

## Benefits

- Plenty of pressure for most site washing applications
- Heavy duty and proven reliability
- Maximum protection for a rental environment
- Reduced speed for cooler running & improved longevity
- Power, reliability & robust strength
- Great protection for a rental & construction environment
- For safe and secure transport & storage
- Simple connectivity for easy use of various cleaning products

## Specification

Engine		Engine Speed (RPM)	3250
Make	Yanmar	Cooling	Air
Type	L100	Fuel Consumption @ 75% Load (Litres/hour)	1.5
Fuel	Diesel / HVO (HVO = BS EN 15940:2016 Only)	Fuel Tank Capacity (Litres)	5.5
Number of Cylinders	1	Average Runtime (Hours) @ 75% Load	3.6
Power (HP)	10	Starting System	Electric

Performance		Max Pressure	3000 PSI/ 200 Bar
Pump Brand	Interpump	Max Flow	15 Ltr per Min/ 4 Gal per Min
Pump Model	Piston Type/WS201	Hose Length	10m
Drive	Gearbox @1450rpm	Noise Level	LWA=99 dBa@7m=74

Technical		Design Approval	UK Standard
Capacity (full)	2000 Litre / 450 Gallon	Bund Material (thickness)	7mm
Fluid	Site Water Only	Inner Tank (thickness)	7mm

Dimensions (With Road-Tow Kit)		
Length: 4090 mm	Width: 1982 mm	Height: 1600 mm
Dry Weight (No Water): 715 kg	Wet Weight (Water Full): 2800 kg	

For more details call **MHM TODAY** on **0808 168 9099**  
 Email [sales@mhm-group.co.uk](mailto:sales@mhm-group.co.uk) or visit us at [www.mhm-group.co.uk](http://www.mhm-group.co.uk)

