

MG 4000 SD-5/ES - Tin 12

4kVA Tin 12 Diesel Generator

When looking for robust, reliable, good quality 4kVA Tin 12 diesel generator, look no further than our MG 4000 SD-5/ES - Tin 12. Fusion models are designed to suit Tin 12 gas and water applications for butt + electro boxes - 110V CTE.

4kVA (110V) AC Aux Power

Linz alternator

Kohler/Lombardini diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Complete with trolley kit + folding handles

Only 84kg

Complete with electric starting system

Features Benefits

Plenty of power to run small gas and water applications

Heavy duty and proven reliability

Electric start, power, reliability and robust strength

Suitable to run off either diesel, HVO or a mixture of both fuels

For nice and easy manoeuvrability and storage

Lightweight design

Effort-free start up



Specification

Performance

Alternator	Linz	Noise Level LWA	=
Single Phase Power (110V)	4kVA/ 3.2kW	Insulation Class	
Single Phase Power (230V)	N/A	Mechanical Protection - IF)

Engine	
Make	Kohler/ Lombardini
Type 15LD350 (Stage 5)	
Fuel Diesel / HVO (HVO = BS EN 15940:2016 Only)	
Number of Cylinders 1	
Power (HP) 6.5	
Engine Speed (RPM	3000

Cooling	Air
Fuel Consumption @ 75% Load (Litres/hou	r) 1
Fuel Tank Capacity (Litres)	13
Average Runtime @ 75% Load (Hours)	13
CO2 Output Per Hour @ 75% Load	2.62kg
Starting System	Electric

LWA=95 dBa@7m=70

Н

23

Dimensions (Machine only)

Length: 765 mm	Width: 525 mm	Height: 590 mm
Dry Weight (No Fuel): 91 kg		Wet Weight (Fuel Full): 104 kg

Dimensions (Trolley kit with handles folded out)

Length: 1460 mm	Width: 750 mm	Height: 725 mm
Dry Weight (No Fuel): 96 kg		Wet Weight (Fuel Full): 109 kg

Cooket Confimuetion	1ph (110V)	
Socket Configuration	32A	16A
MG 4000 SD-5/ES - Tin 12	1	2

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk











