

MG 10000 SSKH-5

Ready to Rent 10kVA Diesel Generator

When looking for a robust, reliable, good quality 10kVA diesel generator, look no further than our MG 10000 SSKH-5.



Optional extras:





Features Benefits

10kVA (230V / 110V) AC Aux Power

Linz alternator

Kohler diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM engine protection shutdown system

Emergency stop button

Central lifting eye and front & side fork pockets

Fully bunded base (110%)

Complete with trolley kit + folding handles

Plenty of power to meet the demands of small generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure and battery charge failure

A must on any UK site

Flexible and safe lifting on site

To retain all spilt fluids

For nice and easy manoeuvrability, transport and storage

Water Cooled Extra Super

Engine



2 Year Engine Warranty (Limited)



Specification

Performance

| Alternator | Linz |
|---------------------------|-----------|
| Single Phase Power (110V) | 10kVA/8kW |
| Single Phase Power (230V) | 10kVA/8kW |
| | |
| | |

| Noise Level | LWA=89 | dBa@7m=64 |
|--------------------|----------|-----------|
| Insulation Class | | Н |
| Mechanical Protect | ion - IP | 23 |

| Engine | | | |
|---|------------------|--|--|
| Make | Kohler | | |
| Туре | KDW702 (Stage 5) | | |
| Fuel Diesel / HVO (HVO = BS EN 15940:2016 Only) | | | |
| Number of Cylinders | 2 | | |
| Power (HP) | 14 | | |
| Engine Speed (RPM) | 3000 | | |
| Cooling | Water | | |
| | | | |

| Fuel Consumption @ 75% Load (Litres/hour) | | | ır) 2.8 |
|---|---|------------|---------|
| Fuel Tank Capacity (Litres) | | | 35 |
| Average Runtime (Hours) | | | |
| @ 100% Load | 9 | @ 75% Load | 12.5 |
| @ 50% Load | 20 | @ 25% Load | 42 |
| CO2 Per Hour @ 75% Load 7 | | | 7.34kg |
| Starting System | Starting System Deepsea 3110 c/w two wire Auto Start/ Stop facility | | |

| Length: 1370 mm | Width: 760 mm | Height: 910 mm |
|------------------------------|---------------|--------------------------------|
| Dry Weight (No Fuel): 364 kg | | Wet Weight (Fuel Full): 393 kg |
| | | |

Dimensions (Trolley kit with handles folded out)

| Length: 1785 mm | Width: 1030 mm | Height: 1050 mm |
|------------------------------|----------------|--------------------------------|
| Dry Weight (No Fuel): 379 kg | | Wet Weight (Fuel Full): 408 kg |

Dimensions (With road-tow kit)

| Length: 2650 mm | Width: 1300 mm | Height: 1270 mm |
|------------------------------|----------------|--------------------------------|
| Dry Weight (No Fuel): 499 kg | | Wet Weight (Fuel Full): 528 kg |

| Socket | 1ph (230V) | | 1ph (110V) | |
|--------------------|------------|-----|------------|-------|
| Configuration | 32A | 16A | 32A | 16A |
| MG 10000 SSKH-5 | 1 | 2 | 2 | 1 |
| Hard wire facility | 1ph (230V) | | 1ph (| 110V) |
| MG 10000 SSKH-5 | V | | V | |

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk











