

MG 8000 SSK

Ready to Rent 8kVA Diesel Generator

When looking for a robust, reliable, good quality 8kVA diesel generator, look no further than our MG 8000 SSK.



Optional extras:





Water Cooled Extra Super Silent



Kいりっtっ **2 Year Engine Warranty** (Limited)

Features

8kVA (230V / 110V) AC Aux Power

Linz alternator

Kubota diesel engine (Stage 3)

HVO (Hydrotreated Vegetable Oil) fuel approved

Exclusive MHM engine protection shutdown system

Emergency stop button

Central lifting eye and front & side fork pockets

Fully bunded base (110%)

Complete with trolley kit + folding handles

Benefits

Plenty of power to meet the demands of small generator hire

Heavy duty and proven reliability

World class performance and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

In the case of low fuel, low oil pressure and battery charge failure

A must on any UK site

Flexible and safe lifting on site

To retain all spilt fluids

For nice and easy manoeuvrability, transport and storage



Specification

Performance

Alternator	Linz
Single Phase Power (110V)	8kVA/ 6.4kW
Single Phase Power (230V)	8kVA/ 6.4kW

Noise Level	LWA=89	dBa@7m=64	
Insulation Class		Н	
Mechanical Protection - IP		23	

Engine	
Make	Kubota
Туре	D722E (Stage 3)
Fuel Diesel / HVO (HVO:	= BS EN 15940:2016 Only)
Number of Cylinders	3
Power (HP)	17
Engine Speed (RPM)	3000

Cooling		Water
Fuel Consumption @	75% Load (Litres/hour)	2.4
Fuel Tank Capacity (L	itres)	40
Average Runtime@ 7	5% Load (Hours)	16
CO2 Output Per Hour	@ 75% Load 6	.29kg
Starting System Deepsea 3110 c/w two wire Auto Start/ Stop facility		

Length: 1220 mm	Width: 670 mm	Height: 840 mm
Dry Weight (No Fuel): 346 kg		Wet Weight (Fuel Full): 377 kg

Dimensions (Trolley kit with handles folded out)

Length: 1635 mm	Width: 940 mm	Height: 980 mr		
Dry Weight (No Fuel): 361 kg		Wet Weight (Fuel Full): 392 kg		

Dimensions (With road-tow kit)

Length: 2650 mm	Width: 1300 mm	Height: 1200 mm
Dry Weight (No Fuel): 481 kg		Wet Weight (Fuel Full): 512 kg

Socket	1ph (230V)		1ph (110V)	
Configuration	32A	16A	32A	16A
MG 8000 SSK	1	2	2	1
Hard wire facility	1ph (230V)		1ph (110V)
MG 8000 SSK	V		v	/

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk











