Ready To Rent Diesel Generators //



Multi Voltage

400V 230V

# **MGTP 20 SSY-5-MV** Ready to Rent 20kVA Diesel Generator

neady to herit zokva Dieser derictator

When looking for a robust, reliable, good quality 20kVA rental-friendly generator, our MGTP 20 SSY-5-MV has everything the hire market requires.

Benefits

Optional extras:

Road-tow On GPS Telemetry Kit Tracker

### Features

20kVA Multi-Voltage AC Aux Power (400V / 230V / 110V)

#### Linz alternator

Yanmar diesel engine (Stage 5)					
HVO (Hydrotreated Vegetable Oi fuel approved					
Exclusive MHM-Gen engine protection shutdown system					
3 way fuel valve					
12V battery isolator switch					

Emergency stop button Variable RCD ELR bypass switch (activated by key only) Central lifting eye and fork pockets Fully bunded base (110%) Engine oil drain pump Hugely versatile with a massive advantage in the rental market Heavy duty and proven reliability World class performance and watercooled Suitable to run off either diesel, HVO or a mixture of both fuels In the case of low fuel, low oil pressure, high engine temp and battery charge failure Easy connectivity to an external fuel tank

Reduces flat battery breakdowns A must on any UK site

Flexible protection

Turn off the ELR to avoid nusiance tripping when powering electrical motors Flexible and safe lifting on site

To retain all spilt fluids Reducing service time

Three Phase Power (400V)

20kVA/ 16kW

Stage **5** Engine

HV

APPROVED

YANMAR 3 Year Engine Warranty (Limited)

## Specification

### Performance

	T CHIOTHIANCE			milliocimuse	1 OWCI (	2010		
AlternatorLinz (AVR Controlled)Single Phase Power (110V)20kVA/16kW		ed)	Noise Level		LWA=88 dBa	@7m=63		
		kW	Insulation C	ass		Н		
	Single Phase Power (230V)	r (230V) 20kVA/ 16kW		Mechanical Protection – IP			23	
Engine Fuel Consumption @ 75% Load (Litres/hour) 4								
	Make Yanmar Fuel Tank Capacity (Litres)					120		
Type TBA (Stage 5)			Av	Average Runtime (Hours)				
	Fuel Diesel / HVO (HVO = BS EN	15940:2016 Only)	@	100% Load	21	@ 75% Load	26	
	Number of Cylinders	4	@	50% Load	43	@ 25% Load	86	
	Power (HP)	27	CC	CO2 Per Hour @ 75% Load				
	Engine Speed (RPM)	1500	( )	ntral Dan al	Dee	psea 7310 c/w	two wire	
	Cooling	Water	CO	ntrol Panel Auto Start/ Stop facil			op facility	

Dimensions (Machine only)									
Length: 1850 mm	W	idth: <b>970</b> n	nm	Height: <b>1520</b> mm					
Dry Weight (No Fuel): 705	g Wet Weight (Fuel Full): 8				): <b>825</b> kg				
Dimensions (With road-tow kit)									
Length: 3310 mm	Wi	dth: <b>1625</b> (	mm	Height: <b>1950</b> mm					
Dry Weight (No Fuel): 935	kg Wet Weight (Fuel Full): 1055 kg								
Socket	3ph (	3ph (400V)		1ph (230V)		110V)			
Configuration	63A	324	324	164	324	16A			

Configuration	63A	32A	32A	16A	32A	<b>16A</b>
MGTP 20 SSY-5-MV	-	1	2	2	3	1
Hard wire facility	3ph (400V)		1ph (230V)		1ph (110V)	
MGTP 20 SSY-5-MV	<ul> <li>✓</li> </ul>		<ul> <li>✓</li> </ul>		~	

## For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk

