

GW 4/200-DC SINCRO

200A Petrol Welder Gen

Our 200A petrol welder is able to support the most common demands of the hire industry. The simple, robust and reliable design allows the operator to weld and use generator power at the same time.

Features

4kVA	110V	AC	generator	power

4kVA 230V AC generator power

DC Welding range 40–200A

Honda petrol engine (Stage 5)

Simple & robust design

Complete with trolley kit

Benefits

Enough to power 9" grinders Powerful 230V for many applications

Will burn a 5mm rod

Featuring low oil level shutdown

Ideal for a rental environment Nice & easy manoeuvrability



Specification

Performance

Type Sin	cro EW 200 DC
Welding (Amps DC)	200
Duty Cycle (Amps) @ 60% 170	@ 35% 200
Open Circuit Voltage (V)	90
Single Phase Power (110V)	4kVA/ 3.2kW

Single Phase Power (230V) 4kVA/ 3.2kW Max Welding Rods (mm) 5 Noise Level LWA=97 dBa@7m=72 Insulation Class Н Mechanical Protection - IP 23 Remote Control Socket N/A

En	g	in	e

Make	Honda	Cooling	Air
Туре	GX 390 (Stage 5)	Fuel Consumption @ 75% Load (Litres/hour)) 2.7
Fuel	Petrol	Fuel Tank Capacity (Litres)	6.1
Number of Cylinders	1	Average Runtime (Hours) @ 75% Load	2.2
Power (HP)	13	CO2 Per Hour @ 75% Load	6.45kg
Engine Speed (RPM)	3000	Starting System	Recoil

Width: 480 mm	Height: 620 mm	
Dry Weight (No Fuel): 86 kg		
olley kit)		
Width: 640 mm	Height: 765 mm	
	Wet Weight (Fuel Full): 102 kg	
1ph (230V)	1ph (110V)	
16A	16A	
1	1	
	viley kit) Width: 640 mm 1ph (230V) 16A	

Designed in the UK.

built in Italy

For more details call MHM TODAY on 0808 168 9099

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk

Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change.



(in) (0)

Warranty (Limited)