

WELFARE

CABIN

READY

MG 10000 Cube (WELFARE-LONGRUN)

Welfare Cabin Ready 9.8kVA Longrun Diesel Generator

GPS Telemetry

Tracker

w

MG 1

When looking for robust, reliable, good quality 9.8kVA Welfare Ready Diesel Generator, look no further than our MG 10000 Cube (Welfare-Longrun). Specially featuring a 301 litre base fuel tank.

Remote Start/Stop + timer control

Optional extras:

onal Remote Start/Stop

Features

 9.8kVA (230V only)
 P

 AC Aux Power
 C

 Mecc Alte alternator
 F

 Kubota diesel engine
 V

 (Stage 3)
 a

 HVO (Hydrotreated Vegetable
 C

 Oil) fuel approved
 C

 Emergency stop button
 A

 Central lifting eye
 F

 Exclusive MHM-Gen engine
 Ir

 protection shutdown system
 a

 Extremely compact
 Ir

 Extra large base fuel tank
 T

 Welfare cabin ready
 F

Benefits
Plenty of power for most welfare cabin applications
Heavy duty and proven reliability
World class performance, 1500rpm and watercooled
Suitable to run off either diesel, HVO or a mixture of both fuels
A must on any UK site
Flexible and safe lifting on site
In the case of low fuel, low oil pressure, and battery charge failure
Ideal when saving space is important
To enable extremely long run time – 157 hours @ 75% load

Easy fit, plug and play cabin installation

Specification

Performance

		_				
Alternator	Mecc Alte (AVF	()	Noise Level		LWA=79 dBa@	7m=54
Single Phase Power (110V)	N/	A	Insulation C	lass		Н
Single Phase Power (230V)	9.8kVA/ 7.8kW		Mechanical	Protectio	on – IP	23
Engine		Fue	l Consumptio	n @ 75%	Load (Litres/hou	ır) 1.9
Make	Kubota	Fue	l Tank Capacit	y (Litres)		300
Type D1105 (Stage 3)		Ave	Average Runtime (Hours)			
Fuel Diesel / HVO (HVO = BSE	N 15940:2016 Only)	@	100% Load	107	@ 75% Load	157
Number of Cylinders	3	@!	50% Load	250	@ 25% Load	500
Power (HP)	13.7	CO:	CO2 Per Hour @ 75% Load 4.98kg			
Engine Speed (RPM)	1500		Control Panel Deepsea 3110 c/w two wire Auto Start/ Stop facility		wo wire	
Cooling	Water	COL			o facility	

\mathcal{P}
<u> </u>
ר iteo

Dimensions (Machine only)Length: 1115 mmWidth: 800 mmHeight: 1560 mmDry Weight (No Fuel): 465 kgWet Weight (Fuel Full): 708 kgSocket Configuration32AMG 10000 Cube (Welfare-Longrun)2Hard wire facility1ph (230V)

rd wire facility	1ph (230V)
10000 Cube (Welfare-Longrun)	V

Designed in the UK,

For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk

Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change