

MG 20000 Cube (WELFARE)

Welfare Cabin Ready 20kVA Diesel Generator

When looking for robust, reliable, good quality 20kVA Welfare Ready Diesel Generator, look no further than our MG 20000 Cube (Welfare). **FUEL**

WELFARE READY

Optional







Features Benefits

20kVA (230V only)

Linz alternator

Kubota diesel engine (Stage 3)

HVO (Hydrotreated Vegetable Oil) fuel approved

Emergency stop button

Central lifting eye and fork pockets

Exclusive MHM-Gen engine protection shutdown system

Extremely compact

Welfare cabin ready

Plenty of power for most welfare cabin applications

Heavy duty and proven reliability

World class performance, 1500rpm and watercooled

Suitable to run off either diesel, HVO or a mixture of both fuels

A must on any UK site

Flexible and safe lifting on site

In the case of low fuel, low oil pressure, and battery charge failure

Ideal when saving space is important

Easy fit, plug and play cabin installation







くいりっけっ **2 Year Engine Warranty** (Limited)

Specification

Performance

Alternator	Linz (AVR)
Single Phase Power (110V)	N/A
Single Phase Power (230V)	20kVA/ 16kW

Noise Level	LWA=88 dBa@7m=63
Insulation Class	Н
Mechanical Protection	on - IP 23

Engine

Make	Kubota
Туре	V2203 (Stage 3)
Fuel Diesel / HVO (HVO	= BS EN 15940:2016 Only)
Number of Cylinders	4
Power (HP)	TBA
Engine Speed (RPM)	1500
Cooling	Water

	-		,	
Fuel Tank Capacity (Litres)			120	
Average Runtime (Hours)				
@ 100% Load	22	@ 75% Load	29	
@ 50% Load	41	@ 25% Load	79	
CO2 Per Hour @ 75% Load 1			11.01kg	
Control Panel Deepsea 3110 c/w two wire Auto Start/ Stop facility				

Fuel Consumption @ 75% Load (Litres/hour) 4.2

Dimensions (Machine only)

Length: 1500 mm

MG 20000 Cube (Welfare)

Dry Weight (No Fuel): 736 kg	Wet Weight (Fuel Full): 856 kg			
Socket Configuration	1ph (230V)			
	125A	63A	32A	16A
MG 20000 Cube (Welfare)	1	1	1	1
Hard wire facility	1ph (230V)			

Width: 815 mm

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk





Height: 1450 mm







