## Event Ready Diesel Generators //



80LWA /

HV

## MGTP 45 USKH-5 Event Ready 45kVA Diesel Generator

When looking for a robust, reliable, good quality ultra silenced 45kVA generator, our MGTP 45 USKH-5 has everything the event market requires.

((0))

**Bund Alarm** 

**GPS** Telemetry

Benefits

Tracker

Optional extras:

Features

Road-tow

Kit

45kVA 3ph (400V)

Linz alternator	
Kohler diesel engine (Stage 5)	
HVO (Hydrotreated Vegetable Oil) fuel approved	
Exclusive MHM-Gen engine protection shutdown system	
3 way fuel valve	-
12V battery isolator switch	-
Emergency stop button	
Central lifting eye and fork pocket	S
Variable RCD	
ELR bypass switch (activated by key only)	
Fully bunded base (110%)	-
Engine oil drain pump	_

Plenty of power to meet the demands of small to medium event hire Heavy duty and proven reliability World class performance and watercooled Suitable to run off either diesel. HVO or a mixture of both fuels In the case of low fuel, low oil pressure, high engine temp and battery charge failure Easy connectivity to an external fuel tank Reduces flat battery breakdowns A must on any UK site Flexible and safe lifting on site Flexible protection Turn off ELR to avoid nusiance tripping when powering electrical motor, or other similar equipment To retain all spilt fluids

Reducing service time



## Specification

Performance			Three Phase Pov	ver (4	400V)	45KVA/36kW
Alternator Linz (AVR Cor	trolled)		Noise Level		LWA=80	dBa@7m=55
Single Phase Power (110V)	N/A	_	Insulation Class			N/#
Single Phase Power (230V) 15KV	A/12kW		Mechanical Prot	ectio	n - IP	23
Engine		Fu	el Consumption @	75%	6 Load (Liti	res/hour) 8.3
Make Koł	iler	Fue	l Tank Capacity (Li	tres)		240
Type KDI2504TCR CAC (Stage	25)	Ave	erage Runtime (Ho	urs)		
Fuel <b>Diesel / HVO</b> (HVO = BS EN 15940:2016 (	) Dnly)	@`	100%	22	@75%	29
Number of Cylinders	4	@_	50%	43	@ 25%	59
Power (HP)	BA	(0)	2 Per Hour @ 75%	Load	ł	21.7 kg
Engine Speed (RPM) 15	500	Car	stral Dan al	Dee	psea 7310	c/w two wire
Cooling Wa	iter	COL	ntrol Panel		Auto Star	t/ Stop facility

Dimensions (Machine	e only)							
Length: <b>2300</b> mm	Width:	980 mm	Height: <b>1450</b> mm					
Dry Weight (No Fuel): <b>1600</b> kg			Wet Weight (Fuel Full): 1795 kg					
Dimensions (With road-tow kit)								
Length: TBA mm	Width:	TBA mm	Height: <b>TBA</b> mm					
Dry Weight (No Fuel): TBA kg Wet Weight (Fuel Full): TBA kg								
Socket	3ph (400V)		1ph (230V)					
Configuration	63A	32A	32A	16A				
MGTP 45 USKH-5	1	1	4	2				
Hard wire facility	3ph (400V)		1ph (230V)					
MGTP 45 USKH-5	1		1					

## For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk



