

MG 6000 SSY-5 - Tin 12 6kVA Tin 12 Diesel Generator

When looking for a robust, reliable, good quality 6kVA diesel generator, look no further than our MG 6000 SSY–5 – Tin 12.

Optional extras:	GPS Telemetry Tracker	IVO UEL	Stage 5		1AR
Features	Benefits	PPROVED	Engine	3 Year Er Warranty (I	
6kVA (110V only) AC Aux Power	Plenty of power to meet the demands of small to medium gas and water applications				
Linz alternator	Heavy duty, proven reliability and extra smooth wave form	MELAN GEN			
Yanmar electric start diesel engine (Stage 5)	Power, reliability and robust strength		Rote		
HVO (Hydrotreated Vegetable Oil) fuel approved	Suitable to run off either diesel, HVO or a mixture of both fuels			NAM / warman / long // 2017/2017/2017/2017/2017/2017/2017/2017/	
Exclusive MHM engine protection shutdown system	In the case of low fuel, low oil pressure and battery charge failure				
Emergency stop button	A must on any UK site	M -23			
Central lifting eye and front & side fork pockets	Flexible and safe lifting on site				
Fully bunded base (110%)	To retain all spilt fluids				
Complete with trolley kit + folding handles	For nice and easy manoeuvrability, transport and storage			Sup	ar

Specification

Performance

Alternator	Linz	z Noise Level LWA=90 dBa@7m=	=65
Single Phase Power (110V)	6kVA/ 4.8kW	Insulation Class	Η
Single Phase Power (230V)	N/A	Mechanical Protection – IP	23
Engine		Cooling	Air
Make	Yanmar	Fuel Consumption @ 75% Load (Litres/hour)	1.4
Туре L100	AE (Stage 5)	Fuel Tank Capacity (Litres)	
Fuel Diesel / HVO (HVO = BS EN	15940:2016 Only)	Average Runtime @ 75% Load (Hours)	18
Number of Cylinders	1	CO2 Output Per Hour @ 75% Load 3.6	7kg
Power (HP)	10	Ctarting System Deepsea 3110 c/w two v	vire
Engine Speed (RPM)	3000	Starting System Auto Start/ Stop faci	

Dimensions (Machine only)

Length: 1050 mm	Width: 590 mm	Height: 750 mm			
Dry Weight (No Fuel): 182 kg		Wet V	Veight (Fuel Full): 203 kg		
Dimensions (Trolley kit v	vith handles folded	out)			
Length: 1570 mm	Width: 760 mm Height: 980 mm				
Dry Weight (No Fuel): 207 kg			Wet Weight (Fuel Full): 228 kg		
Dimensions (With road-t	ow kit)				
Length: 2405 mm	Width: 1045 mm Height: 1190		Height: 1190 mm		
Dry Weight (No Fuel): 312 kg		Wet Weight (Fuel Full): 333 kg			
Socket Configuration		1ph (110V)			
Socket configuration	32A		16A		
MG 6000 SSY–5 – Tin 12	1		2		

Designed in the UK,

built in Italy

For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk

(in)

GF