

MG 4000 SD-5

Ready to Rent 4kVA Diesel Generator

When looking for a robust, light weight, good quality 4kVA diesel generator, look no further than our MG 4000 SD-5 (Recoil Start).



Features Benefits

4kVA (230V / 110V) AC Aux Power

Linz alternator

Kohler/Lombardini diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Complete with trolley kit + folding handles

Only 83kg

Recoil starting system

Plenty of power to run a variety of tools on site

Heavy duty and proven reliability

Recoil start, power, reliability and robust strength

Suitable to run off either diesel, HVO or a mixture of both fuels

For nice and easy manoeuvrability and storage

Lightweight design

Simple and easy start



Specification

Performance

| Alternator | Linz |
|---------------------------|-------------|
| Single Phase Power (110V) | 4kVA/ 3.2kW |
| Single Phase Power (230V) | 4kVA/ 3.2kW |

| Noise Level | LWA=95 | dBa@7m=70 |
|-----------------------|---------|-----------|
| Insulation Class | | Н |
| Mechanical Protection | on - IP | 23 |
| | | |

| Kohler/ Lombardini | | |
|--|--|--|
| 15LD350 (Stage 5) | | |
| Fuel Diesel / HVO (HVO = BS EN 15940:2016 Only) | | |
| 1 | | |
| 6.5 | | |
| 3000 | | |
| | | |
| | | |

| Cooling | Air |
|---|--------|
| Fuel Consumption @ 75% Load (Litres/hou | r) 1 |
| Fuel Tank Capacity (Litres) | 13 |
| Average Runtime@ 75% Load (Hours) | 13 |
| CO2 Output Per Hour @ 75% Load | 2.62kg |
| Starting System | Recoil |

Dimensions (Machine only)

MG 4000 SD-5

| Configuration | 32A | 16A | 32A | 16A | | | |
|--|------------|--------------------------------|----------------|-------------------------|--|--|--|
| Socket | 1ph (230V) | | 1ph (| 110V) | | | |
| | | | | | | | |
| Dry Weight (No Fuel): 88 kg | | Wet Weight (Fuel Full): 101 kg | | | | | |
| Length: 1460 mm | Width: 7 | 750 mm | Height: 725 mm | | | | |
| Dimensions (Trolley kit with handles folded out) | | | | | | | |
| | | | | | | | |
| Dry Weight (No Fuel): 83 kg | | | Wet Weight (Fu | iel Full): 96 ka | | | |
| Length: 765 mm | vviatn: : | 25 mm | He | ignt: 590 mm | | | |

For more details call MHM TODAY

on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk











