

WELFARE

CABIN

READY

Martin - 12 12 12 18

MG 10000 SSK (WELFARE)

Welfare Cabin Ready 9.8kVA Diesel Generator

When looking for robust, reliable, good quality 9.8kVA Welfare Ready Diesel Generator, look no further than our MG 10000 SSK (Welfare).

Optional extras:



aı

lr

aı

Remote Start/Stop + timer control GPS Telemetry Tracker

Features

9.8kVA (230V only)

- Linz alternator Kubota diesel engine 3000rpm (Stage 3)
- HVO (Hydrotreated Vegetable
- Oil) fuel approved
- Emergency stop button
- Central lifting eye and fork pockets
- Exclusive MHM-Gen engine

protection shutdown system

Welfare cabin ready

| Benefits |
|--|
| lenty of power for most welfare abin applications |
| leavy duty and proven reliability |
| Vorld class performance nd watercooled |
| uitable to run off either diesel, HVO r a mixture of both fuels |
| must on any UK site |
| lexible and safe lifting on site |
| n the case of low fuel, low oil pressure, nd battery charge failure |
| asy fit, plug and play cabin installation |

Ст





HVO

FUEL

APPROVED



OIL DRAIN



Specification

Performance

| renormance | | | | | | |
|--------------------------------|--------------------|-----|--|-----------|------------------|---------------|
| Alternator | Lin | z | Noise Level | | LWA=89 dBa@ | 7m=64 |
| Single Phase Power (110V) | N/A | | Insulation Class | | | Н |
| Single Phase Power (230V) | V) 9.8kVA/ 7.8kW | | Mechanical F | Protectio | on – IP | 23 |
| Engine | | Fue | l Consumption | @ 75% | Load (Litres/hou | r) 2.8 |
| Make | Kubota | Fue | Fuel Tank Capacity (Litres)40 | | | |
| Type D72 | 22E (Stage 3) | Ave | Average Runtime (Hours) | | | |
| Fuel Diesel / HVO (HVO = BS EM | l 15940:2016 Only) | @ | 00% Load | 11 | @ 75% Load | 14 |
| Number of Cylinders | 3 | @ 4 | 50% Load | 22 | @ 25% Load | 44 |
| Power (HP) | 17 | CO2 | 2 Output Per Hour @ 75% Load 7.34kg | | | |
| Engine Speed (RPM) | 3000 | Cto | Starting System Deepsea 3110 c/w two wire Auto Start/ Stop facility | | | |
| Cooling | Water | Sld | | | Auto Start/ Stop | o facility |
| | | | | | | |

| Dimensions (Machine only) | | | | | | |
|-------------------------------------|---------------|---------------------------------------|--|--|--|--|
| Length: 1220 mm | Width: 670 mm | Height: 840 mm | | | | |
| Dry Weight (No Fuel): 350 kg | | Wet Weight (Fuel Full): 381 kg | | | | |

| Socket Configuration | 1ph (230V) | | |
|------------------------|------------|-----|--|
| Socket Configuration | 32A | 16A | |
| MG 10000 SSK (Welfare) | 1 | 2 | |
| Hard wire facility | 1ph (230V) | | |
| MG 10000 SSK (Welfare) | V | | |

Designed in the UK,

built in Italy

For more details call **MHM TODAY** on **0808 168 9099**

Email sales@mhm-group.co.uk or visit us at www.mhm-group.co.uk

Picture shown for illustration purposes only. Actual product may differ in appearance. All specifications are subject to change.

(in) (O)

GROI

f)(y)